

Check Snoots

UL Listed



Description

Typically used on multiple inlet fire department connections to help prevent backflow of water into connected supply lines. Manufactured of cast brass* and available in two finishes. Select polished brass or polished chrome. Breakable caps or a male NST plug should be installed to protect swivels and prevent debris from being accidentally introduced into the water way. UL Listed

Installation

Installation of the Check Snoot is achieved with readily available jobsite tools. Prior to installation make sure the proper identification sign has been installed on the nipple.

Coat male threads liberally with a suitable pipe thread sealant such as Pipefit®. Tighten FDC one full turn past hand tight. Make sure FDC is aligned according to requirements.

DO NOT OVER TIGHTEN. OVERTIGHTENING MAY CAUSE SEVERE STRETCHING AND POSSIBLE CRACKING OF THE OF THE FDC BODY.

Specifications

Material:

ASTM B16 C36000
Cast Brass*

Finish:

Rough Brass

Outlet: 3" Male or FNPT

Swivel:

NST	3.0686 x 7.5T
CF	2.9900 x 7.5T
BCT	3.0000 x 8 TP
NYFD	3.0300 x 8 TP
QST	3.0310 x 7 TP
CIN-new	3.0580 x 6 TP
PHX	3.0620 x 6 TP
TEM	3.0750 x 6 TP
CLV	3.0780 x 8 TP
CIN-old	3.0930 x 6 TP
ONT	3.1250 x 5 TP
DET	3.1250 x 7.5T
NovaSCO	3.2300 x 5 TP
Dayton	3.2340 x 6 TP
Richmon	3.3120 x 8 TP
Raleigh	3.3400 x 6 TP

*Contains lead. Not for use in water systems intended for human consumption.

Approvals:

UL Listed 175 psi

